



O型圈 S番 规格表1  
(圆筒面固定、平面固定)



| 编号称呼   | O型圈尺寸             |                   |
|--------|-------------------|-------------------|
|        | 线径 d <sub>2</sub> | 内径 d <sub>1</sub> |
| *S 2   | 1.5±0.1           | 1.5               |
| S 3    |                   | 2.5               |
| S 4    |                   | 3.5               |
| S 5    |                   | 4.5               |
| S 6    |                   | 5.5               |
| S 7    |                   | 6.5               |
| S 8    |                   | 7.5               |
| S 9    |                   | 8.5               |
| S 10   |                   | 9.5               |
| S 11.2 |                   | 10.7              |
| S 12   |                   | 11.5              |
| S 12.5 |                   | 12                |
| S 14   |                   | 13.5              |
| S 15   |                   | 14.5              |
| S 16   |                   | 15.5              |
| S 18   |                   | 17.5              |
| S 20   |                   | 19.5              |
| S 22   |                   | 21.5              |
| S 22.4 | 2.0±0.1           | 21.9              |
| S 24   |                   | 23.5              |
| S 25   |                   | 24.5              |
| S 26   |                   | 25.5              |
| S 28   |                   | 27.5              |
| S 29   |                   | 28.5              |
| S 30   |                   | 29.5              |
| S 31.5 |                   | 31                |
| S 32   |                   | 31.5              |
| S 34   |                   | 33.5              |
| S 35   |                   | 34.5              |
| S 35.5 |                   | 35                |
| S 36   |                   | 35.5              |
| S 38   |                   | 37.5              |
| S 39   |                   | 38.5              |
| S 40   |                   | 39.5              |
| S 42   |                   | 41.5              |
| S 44   |                   | 2.0±0.1           |
| S 45   | 44.5              |                   |
| S 46   | 45.5              |                   |
| S 48   | 47.5              |                   |
| S 50   | 49.5              |                   |
| S 53   | 52.5              |                   |
| S 55   | 54.5              |                   |
| S 56   | 55.5              |                   |
| S 60   | 59.5              |                   |
| S 63   | 62.5              |                   |

| 编号称呼   | O型圈尺寸             |                   |
|--------|-------------------|-------------------|
|        | 线径 d <sub>2</sub> | 内径 d <sub>1</sub> |
| S 65   | 1.5±0.1           | 64.5              |
| S 67   |                   | 66.5              |
| S 70   |                   | 69.5              |
| S 71   |                   | 70.5              |
| S 75   |                   | 74.5              |
| S 80   |                   | 79.5              |
| S 85   |                   | 84.5              |
| S 90   |                   | 89.5              |
| S 95   |                   | 94.5              |
| S 100  |                   | 99.5              |
| S 105  | 104.5             |                   |
| S 110  | 109.5             |                   |
| S 112  | 111.5             |                   |
| S 115  | 114.5             |                   |
| S 120  | 119.5             |                   |
| S 125  | 124.5             |                   |
| S 130  | 129.5             |                   |
| S 132  | 131.5             |                   |
| S 135  | 134.5             |                   |
| S 140  | 139.5             |                   |
| S 145  | 144.5             |                   |
| S 150  | 149.5             |                   |
| *S 155 | 2.0±0.1           | 154.5             |
| *S 160 |                   | 159.5             |
| *S 165 |                   | 164.5             |
| *S 170 |                   | 169.5             |
| *S 175 |                   | 174.5             |
| *S 180 |                   | 179.5             |
| *S 185 |                   | 184.5             |
| *S 190 |                   | 189.5             |
| *S 195 |                   | 194.5             |
| *S 200 |                   | 199.5             |
| *S 205 | 204.5             |                   |
| *S 210 | 209.5             |                   |
| *S 215 | 214.5             |                   |
| *S 220 | 219.5             |                   |
| *S 225 | 224.5             |                   |
| *S 230 | 229.5             |                   |
| *S 235 | 234.5             |                   |
| *S 240 | 239.5             |                   |
| *S 245 | 244.5             |                   |
| *S 250 | 249.5             |                   |
| *S 255 | 254.5             |                   |
| *S 260 | 259.5             |                   |
| *S 265 | 264.5             |                   |

O型圈 S番 规格表2  
（圆筒面固定，平面固定）



| 编号称呼   | O型圈尺寸     |          |
|--------|-----------|----------|
|        | 线径 $d_2$  | 内径 $d_1$ |
| *S 270 | 2.0 ± 0.1 | 269.5    |
| *S 275 |           | 274.5    |
| *S 280 |           | 279.5    |
| *S 285 |           | 284.5    |
| *S 290 |           | 289.5    |
| *S 295 |           | 294.5    |
| *S 300 |           | 299.5    |